

# BILLI QUADRA

Our range of boiling and chilled water dispensers are designed and manufactured as energy efficient filtered water systems that offer customers the very best in innovation, superior performance and reliability.



## Water options



Chilled



Boiling

## Configuration



Smallest under counter footprint with largest capacities.



Billi watercooled systems do not require ventilation.

## Compatible dispensers



## Safety first

Billi's Splashfree boiling water delivery electronically varies the water flow, slowing momentarily to eliminate splashing as the water first enters the cup.

All Billi dispensers are also supplied standard with a safety switch to lock boiling water flow when needed.



## Premium filtration

Billi's range of premium filters are equipped with a unique multi-layered structure which provides superior water quality.



## Heat exchange

Billi's unique Heat Exchange Technology recovers the waste heat energy produced in the chilling process to preheat the boiling water. This allows boiling water to reach optimal temperature more efficiently while achieving substantial energy savings.



## Adjustable chilled temperature

A simple adjustable control knob allows the chilled water temperature to be raised to 15°C or lowered to 6°C for perfectly chilled, refreshing drinks, with your required temperature being quickly reached and maintained.

Model	Suggested n. of people	Boiling water delivery cups per hour	Chilled water delivery cups per hour	Power supply (amps)	Height (mm)	Width (mm)	Depth (mm)
Quadra 440	up to 40	150	175	13	340	315	465
Quadra 460	up to 60	180	175	13	340	315	465

1 cup = 170 ml.

### Water cooled or Air cooled options

Billi are the only manufacturer to offer both water-cooled and air-cooled options.

The water-cooled systems utilise Heat Exchange Technology and are more energy efficient than the air-cooled systems, ensuring water usage is minimal.

Billi's air-cooled options generate far less heat than traditional air-cooled systems.

### Power supply

The Billi Quadra 440, and 460 models require a standard 13 amp UK power outlet.

All models are supplied with a 1 metre flex cord and plug.



Quadra Undercounter



XL Levered Dispenser



### Water supply

A single 15mm (1/2") stop-tap with a male thread should be installed in an easily accessible position.

Water supply must be microbiologically safe to drink, with a minimum dynamic water pressure of 250kPa.

# Billi™

Uncompromising Australian design and quality from Billi, owned by Waterlogic®



Waterlogic International Limited and WLI Trading Limited reserve the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo, Firewall and the Firewall logo are trademarks in countries where the Group operates. WLI Trading Ltd licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.

## Call us today

**UK** [www.waterlogic.co.uk](http://www.waterlogic.co.uk)  
+ 44 (0) 333 600 1845  
[enquiries@waterlogic.co.uk](mailto:enquiries@waterlogic.co.uk)

**IRELAND** [www.waterlogic.ie](http://www.waterlogic.ie)  
1800 266 537  
[info@waterlogic.ie](mailto:info@waterlogic.ie)